

# SET UP



# 748

NATRIX

1ST			SPUR			2ND		
<input type="checkbox"/> 58	<input type="checkbox"/> 59	<input type="checkbox"/> 60	<input type="checkbox"/> 53	<input type="checkbox"/> 54	<input type="checkbox"/> 55			

1ST			PINION			2ND		
<input type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 21	<input type="checkbox"/> 22	<input type="checkbox"/> 23			

FRONT		DRIVE TRAIN		REAR	
<input type="checkbox"/> GEAR DIFF	cst	<input type="checkbox"/> GEAR DIFF	cst		
<input type="checkbox"/> ONE WAY		<input type="checkbox"/> SOLID			
<input type="checkbox"/> SPOOL					

### SHOCK ABSORBERS

FRONT		REAR	
<b>OIL</b>	cst	<b>OIL</b>	cst
<b>SPRINGS</b>		<b>SPRINGS</b>	

Open  
 Closed

FRONT				ANTI-ROLL BARS					REAR	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
1.8	2.2	2.5	2.8	1.6	1.8	2.0	2.2	2.5		

FRONT			TYRES		REAR	
RIGHT	LEFT	Controlled Tyre <input type="checkbox"/>	RIGHT	LEFT		
		MAKE				
		SHORE				
		DIAMETER				
		5-MIN WEAR				

### ENGINE

<b>ENGINE</b>		
VERSION	HEADSHIMS	mm
GLOWPLUG	CARB DIA	mm
PIPE	MANIFOLD	
FUEL	NITRO	%

### CENTAX

<b>CLUTCHBELL</b>	ALU <input type="checkbox"/>	STEEL <input type="checkbox"/>
<b>CLUTCHSHOE</b>	YELLOW <input type="checkbox"/>	RED <input type="checkbox"/> BLACK <input type="checkbox"/>
<b>CLUTCH SPRING</b>		<b>CLUTCH BELL GAP</b> mm

### AERODYNAMIC CONFIGURATION

#### BODY

<b>BRAND</b>	<b>TYPE</b>
<b>BODY POSITION</b>	mm
<b>BUMPER HOLES CUT</b>	
<input type="checkbox"/> YES	<input type="checkbox"/> NO

### REMARKS

RACE		DATE	
TRACK		QUALIFYING POSITION	
DRIVER		QUALIFYING TIME	
TRACTION: LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH <input type="checkbox"/>		STARTING POSITION	
TRACK TEMP		AIR TEMP	
		FINAL POSITION	

