

1ST	<b>SPUR</b>				2ND
<input checked="" type="checkbox"/> 48T	<input type="checkbox"/> 49T	<input type="checkbox"/> 50T	<input type="checkbox"/> 44T	<input checked="" type="checkbox"/> 45T	<input type="checkbox"/> 46T

1ST	<b>PINION</b>				2ND
<input type="checkbox"/> 15T	<input checked="" type="checkbox"/> 16T	<input type="checkbox"/> 17T	<input type="checkbox"/> 18T	<input checked="" type="checkbox"/> 19T	<input type="checkbox"/> 20T

<b>CENTAX</b>	
CLUTCHBELL	ALU <input checked="" type="checkbox"/> STEEL <input type="checkbox"/>
CLUTCHSHOE	BLACK <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> RED <input type="checkbox"/>

<b>SHOCK ABSORBERS</b>	
OIL	OIL
700 CST	900 CST
SPRING	SPRING
purple	pink
<input checked="" type="radio"/> OPEN	<input type="radio"/> CLOSED

<b>ANTI-ROLL BARS</b>		WIRE 2.2 Ø
<input checked="" type="checkbox"/> 0°	<input type="checkbox"/> 30°	<input type="checkbox"/> 45°
<input type="checkbox"/> 60°	<input type="checkbox"/> 90°	<input type="checkbox"/> 0°
<input type="checkbox"/> 30°	<input type="checkbox"/> 45°	<input type="checkbox"/> 60°
<input type="checkbox"/> 90°	<input type="checkbox"/> 0°	<input type="checkbox"/> 30°
<input type="checkbox"/> 45°	<input type="checkbox"/> 60°	<input type="checkbox"/> 90°

LEFT	RIGHT	TYRES	LEFT	RIGHT
xceed		MAKE	xceed	
32°	32°	SHORE	35°	35°
mm	mm	DIAMETER	mm	mm
mm	mm	5-MIN WEAR	mm	mm

ENGINE	Novarossi		
VERSION	keep on	HEADSHIMS	std mm
GLOWPLUG	8	CARB DIA	8 mm

EXHAUST	2015
---------	------

FUEL	byron pro	25 %
------	-----------	------

BODY TYPE:	PF 909
------------	--------

BUMPER HOLES CUT:	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
-------------------	---

<b>STIFFENERS</b>	
RIGHT SIDEPLATE:	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
CARBON	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
LEFT SIDEPLATE:	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

<b>REMARKS</b>
ride height on xceed set tools

RACE	BRCA R1	DATE	25-03-2012
TRACK	Wombwell	RESULT	
SURFACE:	<input checked="" type="checkbox"/> ASPHALT <input type="checkbox"/> OTHER SPECIFY	QUALIFYING POSITION	
LAYOUT:	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST	QUALIFYING TIME	
TRACTION:	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	FINAL POSITION	
TRACK TEMP		AIR TEMP	

FRONT	<input checked="" type="checkbox"/> APPLIED	REAR
-------	---	------

R 2°	2° L	CAMBER	R 3°	2.5° L
------	------	--------	------	--------

BRACKET TYPE	TE <input type="checkbox"/> 966 <input checked="" type="checkbox"/>	CONNECTOR TYPE	NONE <input checked="" type="checkbox"/> RUBBER <input type="checkbox"/> ALU <input type="checkbox"/>
SHIMS FRONT	1 mm	REAR	1 mm
TOE-IN	-1°	WHEELBASE	0 <input type="checkbox"/> -1 <input checked="" type="checkbox"/> -2 <input type="checkbox"/> -3 <input type="checkbox"/> -4 <input type="checkbox"/>
CASTER SPACERS	4 mm	FLEX	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
PULLEY	24 <input type="checkbox"/> 25 <input checked="" type="checkbox"/>	TOE-IN	2.5°

FRONT	ACKERMANN	BACK
TRACK WIDTH		
264 mm		254 mm