

## DRIVER, TRACK AND RESULTS

**DRIVER** Mads A. Callesen **COUNTRY** DK **WEATHER** AIR TEMP 20 TRACK TEMP 20  DRY  INTERMEDIATE  WET  
**TRACK** Skanderborg RC **SURFACE**  ASPHALT  CARPET **TRACTION**  LOW  MEDIUM  HIGH **COMMENTS** grey ETS carpet  
**RACE** DRCMU 4 **DATE** 29.1.2017 **QUALY POS.** 9 **QUALY TIME** **STARTING POS.** B1 **FINAL POS.** B1

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF 5000 cst
<input checked="" type="checkbox"/> SPOOL		

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input type="checkbox"/> FRONT <input type="checkbox"/> REAR	<input checked="" type="checkbox"/> NONE <input type="checkbox"/> mm

FRONT	HEAVE DAMPER	REAR
OIL 1800 cst		OIL 2000 cst
SPRINGS Yellow		SPRINGS Red
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>
N HOLES $\emptyset$ mm		N HOLES $\emptyset$ mm

FRONT	ROLL DAMPER	REAR
OIL 2500 cst		OIL 2500 cst
SPRINGS Blue		SPRINGS Blue
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>
N HOLES $\emptyset$ mm		N HOLES $\emptyset$ mm

FRONT	TYRES	REAR
Sorex 28	MAKE AND TYPE	do.
Black	INSERTS	do.
LRP Carpet 2	ADDITIVE	do.
25 min.	ADDITIVE TIMING	25 min.

ELECTRONICS	
<b>BATTERY</b>	
BRAND Arrowmax 65C	CAPACITY 6000 mAh
<b>MOTOR</b>	
BRAND G-Force	TYPE 13,5T S-Extreme TIMING 60
<b>ESC</b>	
BRAND LRP	TYPE Flow Worksteam / Blinky

RATIO CONFIGURATION			
64	PITCH SPUR GEAR	TEETH	100
64	PITCH PINION	TEETH	40
FINAL DRIVE RATIO 5,00		ROLL OUT - mm	

AERODYNAMIC CONFIGURATION	
BODY BRAND Protoform	
BODY TYPE Mazdaspeed 6 LW	
BODY POSITION ca. 10 mm	

**REMARKS**

FLEX: both screws removed in the chassis stiffener.  
 front and rear alu stiffener brace removed.  
 Both dampers mounted reverse to the manual = spring side to the outside of the car.

